



EMI Filter Connectors and Inserts

Filtered MIL-DTL-83723 Connector Part Number Builder

W F O W 1 4 - 0 7 P S N C B 5 - 4 7 3

<p>WEMS Electronics MIL-DTL-83723 TYPE</p> <p>SERIES III THREADED F SERIES III BAYONET G</p> <p>MOUNTING STYLE</p> <p>SINGLE HOLE MOUNT 0 FLANGE MOUNT 1 SOLDER MOUNT 5 PLUG PUSH-PULL 3 PLUG 6 PLUG RFI 7</p> <p>FINISH</p> <p>ELECTROLESS NICKEL F OD CAD W other finishes available, consult factory</p> <p>SHELL SIZE AND INSERT ARRANGEMENT (PER MIL-STD-1554) example: 14-07</p> <p>CONTACT GENDER</p> <p>MALE PINS P FEMALE SOCKETS S</p> <p>CONTACT TERMINATION</p> <p>PC TAIL P SOLDER CUP S WIRE TERMINATION W</p> <p>CONNECTOR POLARIZATION N, 6-9, Y</p>	<p>CAPACITANCE (3 DIGIT) EXAMPLES: 221 220 pF 682 6,800 pF 473 47,000 pF</p> <p>VOLTAGE RATING (STEADY STATE)</p> <p>0 50 VDC 1 100 VDC 2 200 VDC 3 300 VDC 4 400 VDC 5 500 VDC for values over 500, consult factory</p> <p>FILTER LOCATION</p> <p>S SHELL EXTENSION (AS REQUIRED) B BACKSHELL COMPATIBLE</p> <p>FILTER TYPE</p> <p>C CHIP CAPACITOR D DISCOIDAL / TUBULAR CAPACITOR P PI FILTER</p>
--	--



Filtered MIL-DTL-26500 Connector Part Number Builder

W H 1 A 1 4 - 0 7 P S N C B 5 - 4 7 3

<p>WEMS Electronics MIL-DTL-26500 TYPE</p> <p>THREADED H BAYONET J</p> <p>MOUNTING STYLE</p> <p>SINGLE HOLE MOUNT 0 FLANGE MOUNT 1 SOLDER MOUNT 5 PLUG 6</p> <p>FINISH</p> <p>ANODIC A CONDUCTIVE C other finishes available, consult factory</p> <p>SHELL SIZE AND INSERT ARRANGEMENT (PER MIL-STD-1554) example: 14-07</p> <p>CONTACT GENDER</p> <p>MALE PINS P FEMALE SOCKETS S</p> <p>CONTACT TERMINATION</p> <p>PC TAIL P SOLDER CUP S WIRE TERMINATION W</p> <p>CONNECTOR POLARIZATION N, 6-9, Y</p>	<p>CAPACITANCE (3 DIGIT) EXAMPLES: 221 220 pF 682 6,800 pF 473 47,000 pF</p> <p>VOLTAGE RATING (STEADY STATE)</p> <p>0 50 VDC 1 100 VDC 2 200 VDC 3 300 VDC 4 400 VDC 5 500 VDC for values over 500, consult factory</p> <p>FILTER LOCATION</p> <p>S SHELL EXTENSION (AS REQUIRED) B BACKSHELL COMPATIBLE</p> <p>FILTER TYPE</p> <p>C CHIP CAPACITOR D DISCOIDAL / TUBULAR CAPACITOR P PI FILTER</p>
--	--

